




H225M

Technical Data
2016




AIRBUS
HELICOPTERS


SUPER PUMA
(Civil Version)



H215 short airframe




H215




H225

COUGAR
(Military Version)



H215M



H225M

3 Baseline Aircraft Definition

GENERAL

- Crashworthy design fuselage including cockpit and cabin
- Composite material intermediate structure
- Polyurethane white paint and Dinol AV30 re-inforced anti-corrosive treatment
- Mono-coque tail boom with tail rotor protection and stabilizer
- Front part of the tail boom arranged as a storage compartment
- Fuselage upper part used as transmission deck
- Multipurpose sponsons with crashworthy self-sealing fuel tanks
- Fuselage lower part fittable with floatation gear
- Engine cowlings serving as a work platform when in the open position
- High energy absorption, retractable, tricycle landing gear with trailing-arm main landing gear and castoring nose wheel unit
- Built-in jacking and towing points
- Footsteps for climbing to the transmission deck, the cockpit and the cabin
- Provisions for attaching gripping points
- 4 built-in attachment points for lateral external loads
- Structural and electrical capabilities for axial armament
- Fixed parts of armour plating for pilots
- Cable cutter
- Fixed parts for 3.8 tons cargo sling
- Fixed parts for electrical dual hoist (115V AC)
- Fixed parts for external mirrors
- Interior paint : night blue
- Exterior paint: the fuselage is painted following customer paint scheme (polyurethane finish)
- Active Vibration Control System

COCKPIT

- 2 pilot and copilot crashworthy seats adjustable in height and fore-and-aft, complete with safety belts and extensible shoulder harnesses
- 1 third crew man jump-seat with a 3 point extensible safety harness
- 3 sun visors
- Dual flight control
- Steadying rods at pilot station
- Engine controls
- Master cut-off switches
- Rotor brake control
- Landing gear control
- Differential wheel brakes at pilot and copilot stations
- 2 map cases on pilot and copilot doors
- 1 Flight Manual
- Instrument panel and cockpit painted in black
- 1 hand fire extinguisher
- De-iced pilot and copilot windshield panes with wiper
- De-iced cockpit center pane with wiper
- 2 hot air diffusers
- 3 windshield pane demisting ramps
- 4 adjustable ventilation outlets
- Windshield washer
- 2 jettisonable doors and door-stops
- Enlarged cockpit footsteps
- Cockpit green tinted upper panes
- Five 28 V receptacles
- Access to cabin with partitioning curtain

INSTRUMENTS

- 4 multifunction 6" x 8" landscape LCD displays
- 2 display and autopilot control panels
- 1 Integrated Standby Instrument (ISI) for airspeed, altimeter and gyro-horizon back-up display
- 1 redundant Vehicle Monitoring System (VMS) with one redundant Aircraft Management Computer (AMC) and two 4" x 5" LCD displays
- 1 stop watch
- 2 triple tachometers
- 1 warning panel
- 1 fuel circuit control and monitoring panel with 2 fuel content displays
- Emergency Locator Transmitter
- 1 radio altimeter displayed on multifunction LCDs
- 1 AC/DC control box
- 1 engine starting panel
- 1 landing gear position control and monitoring panel
- 2 heated pitot heads and 6 static vents
- 1 ventilation/heating system control
- Instruments units available in English (Altimeter in feet and Airspeed indicator in kts)
- 1 digital intercommunication system – 2 control boxes
- 1 radio management system, with 2 CDU
- 1 VOR/ILS/ADF/MKR receiver
- 1 VOR/ILS/MKR receiver
- 1 DME receiver (twin channel)

CABIN

- Re-inforced floor fitted with 15 cargo tie-down rings, capable of accommodating various types of seat and cabin additional fuel tanks available on option
- 2 sliding double doors and front sliding windows
- 2 observation bubble windows on double cabin sliding doors
- Cabin green tinted windows
- 8 jettisonable windows (including 4 on the sliding doors)
- 1 rear step door
- 1 hand fire-extinguisher
- Upholstery (dark padded cloth)
- Heating and ventilation (upper outlets adjustable for direction and flow, plus bottom adjustable for flow)
- Floor hatch for cargo sling pole
- Fixed parts for 28 troop seat installation
- Structural provisions for casualty installation
- Cabin door handles

POWER PLANT

- 2 Turbomeca Makila 2A1 1776 kW (2382 shp) maximum emergency power, blade shedding, turbines engines in two separate groups with own starting, feeding, lubricating, and cooling systems
- 2 redundant full digital FADEC including a O.E.I. training mode
- 1 fuel system of 2,880 litres (760 US gal.) usable capacity comprising 9 self sealing and crashworthy tanks, arranged in 2 groups, 4 booster pumps, 3 transfer pumps and a low/high fuel warning system. The pipes are of the crashworthy type.
- Provisions for ferrying fuel tanks
- Hover In Flight pressure Refueling (HIFR)
- 2 engine bay fire-detection systems
- 1 two-cylinder selective fire-extinguishing system
- 2 chip detectors
- Multipurpose engine air intakes (anti-sand and anti-ice filters)
- 1 engine flushing device without removal of cowlings
- 1 cycle counting system
- Fixed parts for infra-red suppressors

TRANSMISSION SYSTEM

- 1 main gearbox (MGB) on flexible mountings with 3 chip detectors one of which with fuzzi burner, oil sight gauge, oil temperature and pressure sensors and torquemeter pick-ups, 2 lubrication pumps and independent circuits
- 1 intermediate gearbox with magnetic plug, oil sight gauge and temperature sensor
- 1 tail gearbox with magnetic plug, oil sight gauge and temperature sensor
- 1 main gearbox oil cooling system
- 1 main gearbox oil emergency cooling system
- 1 MGB total loss of oil spray device
- 1 rotor brake
- 2 MGB bay fire detection circuits
- MGB max. oil temperature warning
- MGB mini oil pressure warning
- TGB maxi oil temperature warning

ROTORS AND FLIGHT CONTROLS

- 1 articulated main rotor with 5 composite-material blades equipped with gust and droop stops
- 1 anti-torque rotor with 4 composite-material blades
- 1 flying control system, fitted with 4 dual-body servo-units (3 on the cyclic and collective pitch channels and 1 on the anti-torque rotor pitch control channel) with 2 chamber per body
- Fixed parts for main rotor blade folding system
- 1 dual/duplex digital autopilot associated with 2 flight data computers and back-up capabilities

ELECTRICAL INSTALLATION

- Two 30/40 kVA, 115/200 V, 400 Hz alternators
- One 43 amp.-hr cadmium-nickel battery
- 2 transformer-rectifiers of 200 Amps each
- One 4 amp.-hr stand-by battery
- One 26 V, 400Hz transformer
- 1 cockpit lighting system including :
 - green pedestal and overhead panel integrated lighting
 - integrated instrument panel lighting (NVG compatible)
 - White general lighting (NVG compatible)
 - 1 white extension lamps (NVG compatible)
 - 2 white map lights
 - 1 storm light
- 1 cabin lighting system equipped with 6 LED Dome lights (NVG compatible)
- 1 cabin lighting system equipped with 4 NVG compatible lights
- 6 receptacles for ancillaries (28 V, 15 amp.)
- 1 receptacle for ancillaries (28 V, 25 amp.)
- 2 external power receptacles (AC and DC)
- One 600 W landing light with variable intensity
- 1 infra-red landing light with variable intensity
- 3 position lights
- 1 bi-mode (red/white) high-intensity anti-collision strobe light LED on tail fin (NVG compatible)
- 4 NVG compatible formation lights

HYDRAULIC GENERATION

- 2 independent hydraulic systems :
 - the LH system feeds one of the servo-unit bodies, the autopilot, the landing gear control, the rotor brake and wheel brakes
 - the RH system feeds the other body of the servo-units
- Hydraulic ground couplings
- 1 DC auxiliary electropump on stand-by for the LH system and for supplying sufficient hydraulic pressure for movement of the controls on the ground before starting in high winds
- 1 stand-by electropump for complete lowering of the landing gear
- Provisions for hydro-electric group installation

AIRBORNE KIT ¹

- 6 static vent blanks
- 2 pitot head covers
- 1 engine air-intake protection cover
- 2 engine tail-pipe blanks
- 4 mooring rings
- 2 rough-weather mooring fittings (included on the aircraft)
- Lashing rings for main landing gear
- 1 access ladder
- 1 data case
- 3 jacking ball-joints
- Main blade tie-down
- Fuel bleed line
- 1 stowing bag for the airborne kit

¹ Weight not included in baseline aircraft empty weight.



© AIRBUS HELICOPTERS, Aeroport International
Marseille Provence - 13725 Marignane Cedex -
France

2016 - All rights reserved
Airbus Helicopters' logo and the names of its
products and services are registered trademarks.
Airbus Helicopters reserves the right
to make configuration and data changes
at any time without notice. The facts and
figures contained in this document and
expressed in good faith do not constitute any
offer or contract with Airbus Helicopters.

Designed by AIRBUS HELICOPTERS
Photos: © AIRBUS HELICOPTERS
Cover photo: © Anthony Pecchi - 2011
Printed by SPI (France)

225M AP 16.100.01 E